



10588.1

STANDARD MANUAL CLAMPING

**Material**

Steel, tempered, alloyed and galvanised (black).

**Technical Notes**

Complete with mounting kit.  
Powerful, adjustable height clamp for

milling, press tools and injection mould applications. Clamping force 22 kN to 49 kN depending on size. Low height readily adjustable. Smooth or ribbed clamping pad available. For use in threaded holes (M10, M12, M16, M20) and 12-28mm T-slot

bases.

**Tips**

Torque the screws to the correct specified torque. Clamping force depends on thread lubrication and thread condition.

Order No.	Size	For slot	d <sub>2</sub>	d <sub>4</sub>	d <sub>5</sub>	h <sub>1</sub> min.   max.	h <sub>2</sub>	h <sub>3</sub>	l <sub>1</sub>	l <sub>2</sub>	l <sub>3</sub>	l <sub>4</sub>	Torque to d <sub>1</sub> Nm max.	Torque to d <sub>3</sub> Nm max.	w <sub>1</sub>	w <sub>2</sub>	A/F	Load capacity for static load kN max.	Weight g
10588.W0022	22	12	M10	M12	13	5-38	58	30	65	15-50		11	50	35	45	13	6	22	700
10588.W0023	22	14	M12	M12	13	5-38	58	30	65	15-50		11	50	40	45	13	6	22	700
10588.W0030	30	14	M12	M16	13	6-68	85	36	135	13-110	25	13	100	70	54	18	8	30	2013
10588.W0031	30	18	M16	M16	17	6-68	85	36	135	16-114	28	16	100	150	54	18	8	30	2045
10588.W0032	32	14	M12	M16	13	6-50	78	36	95	12-82	20	12	120	70	54	18	8	32	1462
10558.W0040	40	18	M16	M20	17	6-50	92	42	110	15-95	26	15	150	150	60	20	10	40	2262
10558.W0043	43	18	M16	M20	17	5-80	105	42	155	16-134	32	16	220	150	60	20	10	43	3158
10558.W0049	49	22	M20	M24	21	7-88	125	52	175	19-165	36	19	220	200	75	25	12	49	5928