



## 17100

SUPPORTS & STOPS

### Material

Steel, case-hardened and precision ground in pairs.

### Technical Notes

DIN6364 P. Tolerances:  
 $h_1$  (height) pair tolerance  $tp2 =$  to IT5.

$w_1$  (width) pair tolerance  $tp1 =$  to IT5.  
 Other dimensions to ISO 2768m.

Order No.	$h_1$	$l_1$	Pair tolerance $tp1$	$w_1$	Pair tolerance $tp2$	$h_1$	Standard tolerance $h_1$	Standard tolerance $w_1$	$w_1$	Weight/pair g
17100.W0008	8	63	0.004		0.006		$\pm 0,2$	$\pm 0,1$	2.5	20
17100.W0010	10	63	0.005		0.006		$\pm 0,2$	$\pm 0,1$	3.2	30
17100.W0012	12	63	0.005		0.008		$\pm 0,2$	$\pm 0,1$	4.0	45
17100.W0013	12	100	0.005		0.008		$\pm 0,2$	$\pm 0,1$	4.0	75
17100.W0016	16	63	0.005		0.008		$\pm 0,2$	$\pm 0,1$	5.0	80
17100.W0017	16	100	0.005		0.008		$\pm 0,2$	$\pm 0,1$	5.0	125
17100.W0020	20	63	0.006		0.009		$\pm 0,2$	$\pm 0,2$	6.3	125
17100.W0021	20	100	0.006		0.009		$\pm 0,2$	$\pm 0,2$	6.3	200
17100.W0025	25	100	0.006		0.009		$\pm 0,2$	$\pm 0,2$	8.0	315
17100.W0026	25	160	0.006		0.009		$\pm 0,2$	$\pm 0,2$	8.0	500
17100.W0032	32	100	0.006		0.011		$\pm 0,3$	$\pm 0,2$	10.0	500
17100.W0033	32	160	0.006		0.011		$\pm 0,3$	$\pm 0,2$	10.0	800
17100.W0040	40	100	0.008		0.011		$\pm 0,3$	$\pm 0,2$	12.0	750
17100.W0041	40	160	0.008		0.011		$\pm 0,3$	$\pm 0,2$	12.0	1200
17100.W0050	50	160	0.008		0.011		$\pm 0,3$	$\pm 0,2$	16.0	2000
17100.W0063	63	160	0.009		0.013		$\pm 0,3$	$\pm 0,2$	20.0	3170
17100.W0064	63	250	0.009		0.013		$\pm 0,3$	$\pm 0,2$	20.0	4950
17100.W0080	80	250	0.009		0.013		$\pm 0,3$	$\pm 0,2$	25.0	7900
17100.W0100	100	250	0.011		0.015		$\pm 0,3$	$\pm 0,3$	32.0	12680
17100.W0101	100	400	0.011		0.015		$\pm 0,3$	$\pm 0,3$	40.0	25300