



## 32440

SPRING PLUNGER & DETENT PINS

### Material

Burnished, ground, hardened steel.

### Technical Notes

Striker bushings are used together with spring plungers when a contact surface is required with high resistance. In particular

they are recommended for use with spring plungers equipped with high load value and those with increased spring loads.

### Tips

For dimensions d2 and s, please see corresponding spring plunger. Striker bushes

are for use with Wixroyd nos. 31500, 32100, 32150, 32200 & 32300 see stated ,e' values for each type.

Order No.	d <sub>1</sub> tol. p6	d <sub>2</sub> & s		d <sub>3</sub>	l <sub>1</sub> ±0.05	Weight g
32440.W0004	4	See corresponding plunger table		1.5	5	1
32440.W0006	6	See corresponding plunger table		2.0	8	2
32440.W0008	8	See corresponding plunger table		3.0	10	4
32440.W0010	10	See corresponding plunger table		4.0	12	7
32440.W0012	12	See corresponding plunger table		6.0	14	12
32440.W0016	16	See corresponding plunger table		8.0	18	26

  

Order No.	l <sub>2</sub>	For 32100 e =	For 32150 e =	For 32200 e =	For 32300 e =
32440.W0004	2	M_4 = 0,6	M_4 = 1,1	M_4 = 1,1	-
32440.W0006	2	M_6 = 0,6	M_6 = 1,6	M_6 = 2,1	Ø 5 mm = 0,8
32440.W0008	2	M_8 = 0,9	M_8 = 1,3	M_8 = 2,2	Ø 6 mm = 1,1
32440.W0010	3	M10 = 1,2	M10 = 1,4	M10 = 1,8	Ø 8 mm = 1,2
32440.W0012	3	M12 = 1,2	M12 = 1,7	M12 = 2,2	Ø 10 mm = 1,9
32440.W0016	3	M16 = 1,6	M16 = 2,3	M16 = 2,5	Ø 12 mm = 1,9